

TILLAGE FAMILY

EXAMPLE: 8537 02-21-30

Center Section Width	# of Sections	Implement Width	Disc Coulter Option	Shank Option	Sweep Option
8	5	37'	1	21	30

This example is a 5-section 37' disc-o-vator with standard 20" disc gangs, heavy duty k-flex shanks with 9" sweeps.

Disc Harrow Model	Special Designation	Field Width	Tractor Req. Horsepower	Weight	Transport Height	Transport Width
3323DH	Narrow Center	23' 1"	160-230	12,000	11'	13' 10"
3326DH	Narrow Center	26' 0"	180-260	13,800	12' 4"	13' 10"
3329DH	Narrow Center	28' 9"	200-290	15,000	13' 8"	13' 10"
4330DH	Wide Center	30' 2"	210-300	17,200	12' 4"	17' 10"
4333DH	Wide Center	33' 1"	230-330	18,500	13' 8"	17' 10"
4336DH	Wide Center	35' 11"	250-360	20,000	15'	17' 10"

Disc-o-vator Model	Special Designation	Field Width	Tractor Req. Horsepower	Weight	Transport Height	Transport Width
8315DVN	15' Three-Section VIII - Narrow Transport	15' 11"	115-135	6,650	8' 5"	9' 10"
8318DVN	18' Three-Section VIII - Narrow Transport	18' 3"	135-155	8,000	9' 6"	9' 10"
8321DVN	20' Three-Section VIII - Narrow Transport	20' 7"	155-180	9,200	10' 9"	9' 10"
8324DVN	24' Three-Section VIII - Narrow Transport	24' 1"	180-200	11,000	12' 3"	9' 10"
8321DV	21' Three-Section VIII	20' 7"	165-185	8,925	9' 3"	13' 9"
8324DV	24' Three-Section VIII	24' 1"	180-200	10,200	10' 9"	13' 9"
8326DV	26' Three-Section VIII	26' 5"	200-250	11,050	12' 0"	13' 10"
8328DV	28' Three-Section VIII	28' 9"	225-275	11,890	13' 3"	13' 10"
8333DV	33' Three-Section VIII	33' 5"	250-300	14,025	14' 3"	16' 6"
8537DV	37' Five-Section VIII	36' 11"	280-340	15,392	12' 6"	15' 9"
8544DV	44' Five-Section VIII	43' 11"	320-380	18,320	13' 3"	14' 6"
8548DV	48' Five-Section VIII	47' 5"	340-400	19,968	14' 9"	18' 4"
8552DV	52' Five-Section VIII	52' 1"	375+	21,632	14' 9"	18' 4"

Field Cultivator Model	Special Designation	Field Width	Tractor Req. Horsepower	Weight	Transport Height	Transport Width
6320FC	20' Three-Section VII	20' 7"	115-135	5,678	9'	13' 9"
6325FC	25' Three-Section VII	25' 3"	140-160	6,809	11' 4"	13' 9"
6328FC	28' Three-Section VII	27' 9"	150-170	7,241	12' 6"	13' 9"
6330FC	30' Three-Section VII	29' 11"	160-180	8,400	13' 8"	13' 9"
6332FC	32' Three-Section VII	32' 3"	170-190	8,630	14' 10"	13' 9"
6537FC	37' Five-Section VII	36' 11"	190-210	10,096	12' 6"	13' 9"
6541FC	41' Five-Section VII	41' 7"	190-210	10,741	12' 6"	13' 9"
6544FC	44' Five-Section VII	43' 11"	220-240	10,979	12' 6"	13' 9"
6548FC	48' Five-Section VII	48' 7"	260-300	12,956	13' 8"	13' 9"
7551FC	51' Five-Section VII	50' 11"	310-360	13,155	13' 8"	16' 1"
7556FC	56' Five-Section VII	55' 7"	330-380	14,060	14' 10"	16' 1"
7560FC	60' Five-Section VII	60' 3"	350-400	14,690	16' 0"	16' 1"

Plains Plow Model	Special Designation	Field Width	Tractor Req. Horsepower (25-35HP/Sweep)	# Sweeps	Weight	Transport Height	Transport Width
9322PP	Three-Section II	22' 4"	150-210	6	8,160	12' 6"	13'
9326PP	Three-Section II	26'	180-240	7	9,220	12' 6"	16' 8"
9533PP	Five-Section II	33' 4"	225-315	9	11,500	14' 6"	18'
9540PP	Five-Section II	40' 8"	275-385	11	13,480	13' 6"	18'
9744PP	Seven-Section II	44' 4"	300-420	12	17,300	14' 6"	21' 10"
9748PP	Seven-Section II	48'	325-455	13	18,620	14' 6"	25' 6"
9752PP	Seven-Section II	51' 8"	350-490	14	19,220	14' 6"	21' 10"
9756PP	Seven-Section II	55' 4"	375-525	15	20,540	14' 6"	25' 6"

Seed Bed Conditioner	Field	Tractor Req.	Field	Weight	Transport	Transport
Model	Width	Horsepower	Width		Height	Width
2112SC	12' 6"	1-2 Hp. per ft.	12'11"-13'7"	1,701	N/A	14' 3"
2115SC	15' 0"	1-2 Hp. per ft.	15'5"-16'1"	2,025	N/A	16' 10"
2317SC	17' 6"	1-2 Hp. per ft.	17'1"-18'5"	2,675	7' 11"	15' 0"
2320SC	20' 0"	1-2 Hp. per ft.	19'7"-20'11"	3,040	9' 1"	15' 0"
2322SC	22' 6"	1-2 Hp. per ft.	22'1"-23'5"	3,435	10' 3"	15' 0"
2325SC	25' 0"	1-2 Hp. per ft.	23'9"-25'9"	3,600	11' 5"	15' 0"
2327SC	27' 6"	1-2 Hp. per ft.	26'3"-28'3"	4,200	12' 7"	15' 0"
2330SC	30' 0"	1-2 Hp. per ft.	28'9"-30'9"	4,560	13' 9"	15' 0"
2332SC	32' 6"	1-2 Hp. per ft.	31'3"-33'3"	4,955	13' 9"	17' 6"
2335SC	35' 0"	1-2 Hp. per ft.	33'9"-35'9"	5,320	14' 11"	17' 6"
2536SC	36' 0"	1-2 Hp. per ft.	36'3"-37'9"	6,120	12' 9"	17' 6"
2538SC	38' 6"	1-2 Hp. per ft.	37'7"-40'3"	6,460	12' 9"	17' 6"
2541SC	41' 0"	1-2 Hp. per ft.	39'9"-42'9"	6,970	12' 9"	17' 6"
2543SC	43' 6"	1-2 Hp. per ft.	42'3"-45'3"	7,310	14' 0"	17' 6"
2546SC	46' 0"	1-2 Hp. per ft.	45'0"-47'9"	7,820	14' 0"	17' 6"
2548SC	48' 6"	1-2 Hp. per ft.	47'6"-49'0"	8,160	14' 0"	17' 6"
2551SC	51' 0"	1-2 Hp. per ft.	50'0"-51'6"	8,670	15' 3"	17' 6"

Turbo-Till	Tractor Req.	Field	Weight	Transport	Transport
Model	Horsepower	Width		Height	Width
1200TT	80-100	11' 8"	5,600	N/A	12' 3"
1500TT	100-120	15'	7,420	N/A	15' 7"
1800TT	120-140	17' 8"	9,240	8' 9"	12' 3"
2400TT	165-185	24'	11,240	10' 3"	15' 7"
3000TT	210-240	30'	12,900	13' 5"	15' 7"
4000TT	275-375	40'	16,500	14' 4"	17' 6"

Turbo Chopper	Tractor Req.	Field	Weight	Transport	Transport
Model	Horsepower	Width		Height	Width
1200TC	80-100	11' 8"	5,600	N/A	12' 3"
1500TC	100-120	15'	7,420	N/A	15' 7"
1800TC	120-140	17' 8"	9,240	8' 9"	12' 3"
2400TC	165-185	24'	11,240	10' 3"	15' 7"
3000TC	210-240	30'	12,900	13' 5"	15' 7"
4000TC	275-375	40'	16,500	14' 4"	17' 6"

Turbo Chisel		Tractor Req.	Field		Transport	Transport
Model	Special Designation	Horsepower	Width	Weight	Height	Width
TC5109	9-Shank - Rigid	140-175	11' 3"	8,080	N/A	11' 6"
TC5111	11-Shank - Rigid	160-200	13' 9"	9,835	N/A	14' 3"
TC5113	13-Shank - Rigid	190-230	16' 3"	11,240	N/A	16' 6"
TC5115	15-Shank - Rigid	220-270	18' 9"	12,600	N/A	19' 0"
TC5313	13-Shank - Folding	190-230	16' 3"	11,280	9' 6"	14' 6"
TC5315	15-Shank - Folding	220-270	18' 9"	12,900	10' 3"	14' 6"
TC5317	17-Shank - Folding	250-310	21' 3"	13,700	11' 0"	14' 9"
TC5319	19-Shank - Folding	280-330	23' 9"	14,200	12' 3"	14' 9"
TC5321	21-Shank - Folding	310-360	26' 3"	15,650	13' 6"	14' 9"
TC5323	23-Shank - Folding	350-410	28' 9"	16,250	14' 6"	14' 9"

Ultra-Till		Tractor Req.	Field		Transport	Transport
Model	Special Designation	Horsepower	Width	Weight	Height	Width
UT3030	3-Section	150-200	30'	12,000	14'4"	14'8"
UT5036	5-Section	180-250	36'	14,700	12'8"	16'7"
UT5042	5-Section	200-300	42'	17,450	14'3"	16'7"
UT5052	5-Section	300+	52'	21,500	15'6"	18'11"

Verti-Till		Tractor Req.	Field		Transport	Transport
Model	Special Designation	Horsepower	Width	Weight	Height	Width
VT4360A	4-Shank 36" Auto	275-350	12' 6"	^	6' 6"	13' 0"
VT5300A	5-Shank 30" Auto	250-400	12' 6"	11,198	6' 6"	13' 0"
VT6360A	6-Shank 36" Auto	300-500	18' 0"	^	6' 6"	18' 0"
VT7225A	7-Shank 22 ½" Auto	350-500	13' 1"	11,850	6' 6"	13' 0"
VT7300A	7-Shank 30" Auto	350-500+	17' 6"	12,406	6' 6"	18' 0"
VT9225A	9-Shank 22 ½" Auto	350-500+	16' 11"	11,627	6' 6"	18' 0"

In-Line Sub-Soiler Model	Special Designation	Frame Width	Tractor Req. Horsepower	Field Width	Weight	Transport Height	Transport Width
SS1300A-0330	3-Shank 30" Auto	11' 1"	50-80 per shk	11'-18'	3,170	N/A	11'-18'
SS1300R-0330	3-Shank 30" Rigid	11' 1"					
SS1300A-0336	3-Shank 36" Auto	11' 1"					
SS1300R-0336	3-Shank 36" Rigid	11' 1"					
SS1300A-0338	3-Shank 38" Auto	11' 1"					
SS1300R-0338	3-Shank 38" Rigid	11' 1"					
SS1300A-0340	3-Shank 40" Auto	11' 1"					
SS1300R-0340	3-Shank 40" Rigid	11' 1"					
SS1300A-0424	4-Shank 24" Auto	11' 1"					
SS1300R-0424	4-Shank 24" Rigid	11' 1"					
SS1300A-0430	4-Shank 30" Auto	11' 1"					
SS1300R-0430	4-Shank 30" Rigid	11' 1"					
SS1300A-0436	4-Shank 36" Auto	11' 1"					
SS1300R-0436	4-Shank 36" Rigid	11' 1"					
SS1300A-0438	4-Shank 38" Auto	11' 1"					
SS1300R-0438	4-Shank 38" Rigid	11' 1"					
SS1300A-0440	4-Shank 40" Auto	11' 1"					
SS1300R-0440	4-Shank 40" Rigid	11' 1"					
SS1300A-0530	5-Shank 30" Auto	11' 1"					
SS1300R-0530	5-Shank 30" Rigid	11' 1"					
SS1300A-0624	6-Shank 24" Auto	11' 1"					
SS1300R-0624	6-Shank 24" Rigid	11' 1"					
SS1300A-0824	8-Shank 24" Auto	11' 1"					
SS1300R-0824	8-Shank 24" Rigid	11' 1"					

In-Line Sub-Soiler Model	Special Designation	Frame Width	Tractor Req. Horsepower	Field Width	Weight	Transport Height	Transport Width
SS1700A-0536	5-Shank 36" Auto	14' 3"	50-80 per shk	14'-20'	5,509	N/A	14'-20'
SS1700R-0536	5-Shank 36" Rigid	14' 3"					
SS1700A-0538	5-Shank 38" Auto	14' 3"					
SS1700R-0538	5-Shank 38" Rigid	14' 3"					
SS1700A-0540	5-Shank 40" Auto	14' 3"					
SS1700R-0540	5-Shank 40" Rigid	14' 3"					
SS1700A-0630	6-Shank 30" Auto	14' 3"					
SS1700R-0630	6-Shank 30" Rigid	14' 3"					
SS1700A-0636	6-Shank 36" Auto	17' 10"					
SS1700R-0636	6-Shank 36" Rigid	17' 10"					
SS1700A-0638	6-Shank 38" Auto	17' 10"					
SS1700R-0638	6-Shank 38" Rigid	17' 10"					
SS1700A-0640	6-Shank 40" Auto	19' 6"					
SS1700R-0640	6-Shank 40" Rigid	19' 6"					
SS1700A-0730	7-Shank 30" Auto	17' 10"					
SS1700R-0730	7-Shank 30" Rigid	17' 10"					
SS1700A-0736	7-Shank 36" Auto	19' 6"					
SS1700R-0736	7-Shank 36" Rigid	19' 6"					
SS1700A-0738	7-Shank 38" Auto	21' 2"					
SS1700R-0738	7-Shank 38" Rigid	21' 2"					
SS1700A-0740	7-Shank 40" Auto	21' 2"					
SS1700R-0740	7-Shank 40" Rigid	21' 2"					
SS1700A-0830	8-Shank 30" Auto	19' 6"					
SS1700R-0830	8-Shank 30" Rigid	19' 6"					

NOTE: All specifications are subject to change without notice.