

1510/1550 Flex-Wing Cutters

1510/1550 Flex-Wing Cutters



The 1500 Series features heavy-duty cutting power with a transportable and maneuverable design

- Available for tractors equipped with 1000 or 540 rpm PTOs
- Heavy, adjustable slip clutches protect all three gearboxes
- Available with Cat. V constant velocity input driveline
- 7 gauge decks on center section and wings with ¼" x 10" side skirts
- Three tire options
- Protected by dual spring cushion shock absorbers
- Formed, round stump jumper
- Reversible swivel clevis

Blade Tip Speed	15,000 fpm
Blade Profile	High Lift
Clevis	Reversing Flexible Swivel
Hitch	Pull Type Self Leveling
Cutting Height	1" - 15"
Cutting Width	15'
Cutting Capacity	up to 2" diameter
Deck Material	7 Gauge, Heavy-Duty
Side Skirt Material	¼" x 10" Deep
Minimum Tractor Hp	50 hp
Drive Line Specification	ASAE Category 4 or 5
Gearboxes	4 each at 540 or 1000 rpm
Gearbox Rating	125 hp Main, 100 hp Outboard
Blade Overlap	5½"
Skid Shoes	3 Plate
Wing Fold Angle	90° Up, 22° Down
Overall Weight	3750 lbs.
Slip Clutch Protection	Standard