

Brillion

8' Seedbed Mulch Tucker



The Brillion Mulch Tucker is the ideal tool for the operator who needs to anchor mulch over new seedings. The notched "Tucker Blades" push the hay or straw mulch into the soil on newly seeded areas. The rear roller firms the seedbed and locks the mulch in place to prevent blowing or washing away.

SPECIFICATIONS

- **Frame:** 4" x 4" steel tubing.
- **Axles:** 1-1/2" square axles on tucker blades. 4" O.D. Pipe axles on pulverizer section.
- **Bearings:** Triple sealed, self aligning, flanged bearings.
- **Tucker blades:** Twelve notched, 20" diameter, 3/16" abrasive resistant steel on 8" spacings.
- **Pulverizer Roller:** Twenty four 16" diameter, cast iron notched wheels.
- **Hitch:** Category 1 three point hitch. Floating lower linkage arms allow unit to follow contours.
- **Tractor Requirement:** Minimum 30 HP with lift capacity of 2,000 lbs. located 24" behind the hitch.
- **Fully Reversible:** Three point hitch can be mounted on tucker blade or pulverizer roller frame to pull in either direction.

Model
SMT-8

Overall Width
104"

Working Width
96"

Height
41"

Approx. Weight
1600 lbs.



Brillion Iron Works, Inc.

P.O. Box 127

Brillion, WI 54110-0127

Phone (920) 756-3720

(800) 409-9749

Fax (920) 756-3409

FORM NO. MT-10-N

Specifications subject to change without notice

LITHO U.S.A.

Visit at www.brillionfarmeq.com