



3-POINT MIN-TILL DRILL



MODELS
3P500
3P500V
3P600

Rugged construction with best-in-class accuracy.

5' and 6' Min-Till Drills are designed to get into places big drills simply can't, like orchards and vineyards as well as wooded areas. These units are ground driven and feature a 4-speed gearbox for fast seed rate changes. The rugged opener and press wheel system provide accurate and consistent seed placement. Our seed tube and flap combination makes sure the seed gets to the bottom of the trench and doesn't bounce out like the competition. T-Handle press wheel adjustments allow for small incremental changes in planting depth. Heavy-duty 205mm double disk bearings ensure that you will wear out before your bearings do.



3P500V (Vineyard) Low Profile Box allows for a height of only 50" for work in vineyards and orchards.



Great Plains

5 & 6 FOOT 3-POINT MOUNTED MIN-TILL DRILL



Fluted Feed Cups



Seed Level Indicator



Small Seeds Box (optional)



V-bottom Seed Boxes



4-Speed Gearbox



Positive Ground Drive



Water Tight Lids



Wide Steel Walkboards



Calibration Crank



Cat.1 or Cat.2 Hitch

FEATURES AND BENEFITS

Feature	Benefit
Fluted Feed Cups	Reliable fluted feed design efficiently meters a wide variety of seeds from peas to alfalfa.
Positive Ground Drive	Adjustable ground drive also acts as a gauging wheel.
Water Tight Lids	Lids open wide and stay open for filling and protect seed when closed.
Wide Steel Walkboard	Wide walkboards and step provide easy, safe access to large seed box (optional on 3P500V).
Calibration Crank	Lets you adjust the drill for the most accurate seeding rates.
Cat.1 or Cat.2 Hitch	Provides your choice of hitch to match existing equipment.
Seed Level Indicator	A high visibility seed level indicator can be easily viewed from the tractor.
Small Seeds Box	This attachment utilizes a smaller version of the fluted feed cup to accurately meter seeds.
V-Bottom Seed Boxes	V-bottom seed boxes are designed for complete cleanout.
4-Speed Gearbox	Allows quick and easy changing of drive speed settings.

OPTIONAL EQUIPMENT

Small Seeds	Air Design Disk Scrapers	Keeton Seed Firmer
Seed Cup Plugs	Transport Lights	Acre Meter
Seed-Lok® Firmers	Seed Box Agitator (Std. on 3P500V)	

SPECIFICATIONS

Model Name	3P500		3P500V			3P600	
Row Spacing	6" (15.24cm)	7.5" (19.05cm)	6" (15.24cm)	7.25" (18.4cm)	7.5" (19.05cm)	6" (15.24cm)	7.5" (19.05cm)
Number of Openers	9	7	9	8	7	11	9
Weight	1200 lb (544 kg)		1100 lb (499 kg)			1500 lb (680 kg)	
Working Width	5' (1.52 m)		5' (1.52 m)			6' (1.83 m)	
Transport Width	4' 10" (1.47 m)		4' 10" (1.47 m)			6' 8" (2.03 m)	
Transport Clearance	Varies by tractor lift						
Height	61" (1.55 m)		50" (1.27 m)			61" (1.55 m)	
Length	4' 9" (1.45 m)		4' 9" (1.45 m)			4' 9" (1.45 m)	
Seed Box Capacity	10 bu		8.5 bu			12 bu	
Tire Size	5.7"x 8" (14.48 x 20.32 cm)						
Opener Travel	6.5" (16.51 cm)						
Opener Depth	0 to 3.5" (0 to 8.89 cm)						
Opener Down Pressure	00 Series - 90-180 lbs (40.82 kg to 81.64 kg)						

Note: Weights based on 7.5" spacing and will vary depending on options. Transport clearance will vary depending on tractor.
 **Specifications subject to change at any time.