



# Great Plains

# New Product

## Model SSH Implement Hitch



**T**he Great Plains Pull Hitch is a tough 3-point pull package designed to turn your 3-point implements into pull-types.

Versatility is its middle name! Regardless of what 3-point equipment you may own, this hitch can likely turn it into a pull-type. No longer requiring the normal hassle of hooking and unhooking to the tractor's 3-point hitch.

The rugged design allows it to handle equipment up to 15,000 lbs. It is fully adjustable to handle a wide variety of row spacings. Even the spindles are adjustable so the duals can be set narrow or wide. The 3-point jaws are also adjustable for Cat. 3N or Cat. 3 spacing and can be set rigid or allowed to float.

Our optional 300 gallon tank is available for fertilizer or chemicals. Check out a SSH Implement Hitch today at your local Great Plains Dealer.



SSH Shown With Great Plains 3-Point Sub-Soiler



SSH Shown With Great Plains 20' 3-Point Drill

# Specifications

## SSH Implement Hitch



Dual Lift Wheels



5" Hydraulic Cylinders



Transport Locks



Heavy Duty Turnbuckle



Adjustable Lift Wheel Location



Quick Hitch



Adjustable Cast Hitch



15,000 lbs. Rating



### FEATURES & BENEFITS

FEATURE	BENEFIT
Dual Lift Wheels	Dual 12.5L-15 F-load rated tires provide plenty of footprint for lifting heavy implements
5" and 4 3/4" Hyd. Cylinders	Provides all the lifting power needed for today's heavy 3-point implements
Transport Locks	Create a positive lock-up to eliminate hazards of hydraulic failure during transport
Heavy Duty Turnbuckle	Plated turnbuckle adjusts front to back implement leveling
Adjustable Lift Wheel Location	Allows in and out movement of lift wheels to match up with row spacings
Quick Hitch	Makes hooking up to an implement safer and easier
Adjustable Cast Hitch	Allows hitch height adjustment and unmatched wear resistance
Rated For 15,000 lbs.	Heavy duty hitch to handle the toughest implement challenges

### OPTIONAL EQUIPMENT

300 Gal. Fert. Tank	Tank Mount Only
---------------------	-----------------

### SPECIFICATIONS

Model Name	SSH
Length	14'
Width	Adjustable, 94" Max
Height	
Lift Range	14" to 41"
Weight	3040 lbs.
Dual Wheel Centers	19 7/8" or 24 1/2"
Gauge Wheel Centers	76" to 94"
Quick Hitch Type	Cat. II, Cat III or Cat III
Tire Size	12.5L-15 F-Load
Cylinder Size	5" x 16" Master and 4 3/4" x 16" Slave

P.O. Box 5060 • Salina, Kansas 67402

(785) 823-3276 • FAX (785) 822-5600

Visit us at our web site: <http://www.greatplainsmfg.com>

