

24' & 30' 2-Section No-Till DRILLS



This field proven design is built for the toughest no-till conditions. It features our 10 series opener and coultter combination to precisely place seed in the bottom of the seed groove.

MODELS
2N-2410
2N-3010

Accurate depth control is provided by the direct link press wheel with 18 depth settings in 1/4" increments. The 2.1 bushel per foot seed box and wide stable walk board provide an excellent level of productivity at a reasonable price. These units come standard with point row clutches that allow the operator to seed with one-half the drill width to save seed cost. Options include high flotation skid steer tires, shaft monitor, Keeton seed firmers, flat-fold marker, seed box agitator, and two bar spike harrow.



Great Plains

24' & 30' 2-SECTION NO-TILL DRILL SPECIFICATIONS



Fold For Transport



Four Speed Gearbox



Grease Bank




Electro-Hydraulics



Press Wheel Choices




Frame Mounted Coulters



205 Opener Disk Bearings



Large Seed Box



Electric Point-Row Clutches



Seed Tube And Flap



Optional Weight Brackets

FEATURES & BENEFITS

Feature	Benefit
Fold For Transport	Fold for transport without leaving your tractor seat
Frame Mounted Coulters	450 lbs of coulters preload keep the coulters in the ground and running at the proper depth
205 Opener Disk Bearings	Large 205mm tripple-lip-seal bearings for superior blade life
Large Seed Box	Minimizes stops in the field to increase productivity
Electric Point-Row Clutches	Shuts off drill sections for point-row seeding
Seed Tube And Flap	Guides seed to the bottom of the trench and helps eliminate seed bounce
Optional Weight Bracket	Add additional weight to penetrate tough seeding conditions
Four Speed Gearbox	Makes seed rate changes easy with the lever shifter
Grease Bank	Central location for easy coulters maintenance
Electro-Hydraulics	Lift, fold, and marker functions all controlled with switches in the tractor
Press Wheel Choices	Choose from 4 different press wheels to match your soil and seedbed conditions

OPTIONAL EQUIPMENT

Flat Fold Markers	Keeton Seed Firmers	Small Seeds
Seed Cup Plugs	Weight Brackets	Seed-Lok® Wheels
Choice of Press Wheels	Fluted, Wavy or Turbo Blades	Agitator
Shaft Monitor	Coil Tine Harrow	Air Design Disk Scraper
Flow Monitor	Skid Steer Tires	

SPECIFICATIONS

Model Name	2N-2410	2N-3010
Row Spacing	7 1/2", 10"	7 1/2", 10"
Number of Openers	38, 28	48, 36
Weight	17,400 lbs.	20,200 lbs.
Working Width	24'	30'
Transport Width	17' 1"	17' 1"
Transport Clearance	17"	17"
Height	8' 4"	8' 4"
Length	21' 4"	24' 2"
Seedbox Capacity	48 bu.	60 bu.
Tire Size	12.5 x 15" Transport, 11L x 15" Gauge Wheel	12.5 x 15" Transport, 11L x 15" Gauge Wheel
Opener Travel	10"	10"
Opener Depth Settings	0 to 3.5"	0 to 3.5"
Opener Down Pressure	100 to 140 lbs.	100 to 140 lbs.
Coulters Depth	0" to 4"	0" to 4"
Coulters Pre-Load	450 lbs.	450 lbs.
HP Requirements (est)	140	200

Note: All specifications subject to change without notice.
 *Weights based on 7.5" spacing and will vary depending on options.