



• Photo may show optional equipment not supplied with standard unit.

The true test of an air drill is how accurately it will maintain seed distribution over the full width of the machine. Great Plains No-Till Air Drills combine the efficiency of an air delivery system with the seeding accuracy of the field proven 10 series double disk opener. The 150 bushel Integrated Air Cart makes maneuvering in tight field corners, or backing into the machine shed a snap.

Fourteen tires provide excellent floatation in adverse planting conditions. If you need to cover more acres in less time, chances are it's time to consider the productivity of a Great Plains No-Till Air Drill. We think you'll find it's the most productive no-till air drill you'll ever own.

Features

Features	Transport Lights
High Capacity Fan	Monitors
Wide Steel Walkboard	Gearbox
Opener Features	Acremeter
Weights	

Options

Options	Air Design® Disk Scrapers
Marker	Coulter Options
Coil Tine Harrow	Press Wheel Options
Seed-Lok®	Blockage Monitor

Opener Options

Openers
10 Series

30' No-Till Air Drill w/150bu Cart Specifications

Model Name	NTA3010/ADC1150	
Row Spacing	7.5" (19.05cm)	10" (25.40cm)
Number of Openers	48	36
Weight	22150lbs (10047kg)	
Working Width	30' (9.14m)	
Transport Width	16' 10" (5.13m)	
Transport Clearance	14" (35.56cm)	
Height	12' 6" (3.8m)	
Length	34' 10" (10.62m)	
Seed Box Capacity	150bu	
Tire Size	16.5L x 16.1" Cart, 11L x 15" Imp	
Opener Travel	11" (27.94cm)	
Opener Depth	0 to 3.5" (0 to 8.89cm)	
Opener Down Pressure	100 to 140lbs (45.36 to 63.50kg)	
Coulter Depth	0 to 6" (0 to 15.24cm)	
Coulter Pre-load	450lbs (203kg)	

Note: Weights based on 7.5" spacing and will vary depending on options. Transport clearance will vary depending on tractor.

No one can out maneuver our integrated cart and implement.

Every Great Plains Air Drill features a cart that is fully integrated into the implement design. This exclusive feature makes backing into field corners, irregularly shaped fields, sheds and storage buildings a snap. Take a look at this graphic; it clearly demonstrates that the "multiple pivot points" found on competitive models make backing virtually impossible. Great Plains' added maneuverability turns wasted field corners into productive, highly profitable acreage. Transport length is up to 15' shorter.




Competitive models are typically over 15' longer with multiple pivot points making backing virtually impossible.



Great Plains fully integrated cart design makes backing up a simple procedure.

Pressurized Compartment

By pressurizing the seed compartment, equal pressure is placed on the seed from all sides. This ensures even and accurate feeding of the seed into the air delivery system.



Details that make the difference.

The exclusive interior design of the tower features dimples to break-up airflow ensuring even distribution of seed through the full working width of the machine. The transition cone (shown in red) is critical in providing a smooth transition from the primary tubes to the individual row tubes, eliminating damage to the seed typically encountered on competitive towers.



Weight Transfer

Hydraulic weight transfer allows even distribution of weight across the entire width of the implement. A simple twist of a dial will increase or decrease the transfer of the weight to the wing sections. The cart design means implement function is not effected by the grain bin being empty or full.

