

# NTA2000

## 6 Meter No-Till Air Drill

(Click on Image for Detailed View)



We challenge you to find a no-till seeding system in a 6 meter working width that can compare to the productivity of our 6 meter No-Till Air Drill. The 1850 liter seed box utilizes the efficiency of an air delivery system to deliver seed to the proven double disk openers, in conjunction with our narrow transport width maximizing productivity while minimizing fill times.

### Primary Uses:

For countries with 3 meter (10') transport requirements  
For farms with 200 hectares or more

### Primary Features:

3 Meter Transport  
Hydraulic Weight Transfer  
Center Pivot Design

### Features

(click on a Feature for more information)

[Hectare Meter](#)  
[Simple Calibration](#)  
[Contact Drive Monitor](#)

[High Capacity Fan](#)  
[Coulter Options](#)  
[Infinite Ratio Gearbox](#)

[Disks and Bearings](#)  
[Low velocity seed placement](#)  
[Double Coulter Bar](#)

### Options

(click on an Option for more information)

[Small Seeds Markers Auger](#)

[Coil Tine Harrow](#)  
[Springloaded Scrapers](#)

[Seed-Lok®](#)  
[Hydraulic Brakes](#)

### Opener Options

(click on an Opener Option for more information)

[00 Series](#)

### Specifications

**Model Name**

**NTA2000**

<b>Working Width</b>		<b>6 m</b>	
<b>Transport Width</b>		<b>3 m</b>	
<b>Transport Height</b>		<b>3.35 m</b>	
<b>Transport Length</b>		<b>7.72 m</b>	
<b>Weight</b>		<b>7,460 kg</b>	
<b>Row Spacing</b>	<b>15.1 cm</b>	<b>16.7 cm</b>	<b>19 cm</b>
<b>Number of Rows</b>	<b>40</b>	<b>36</b>	<b>32</b>
<b>Coulter Dimensions</b>		<b>16 mm x 457 mm</b>	
<b>Seed Box Capacity</b>		<b>2850 Liters</b>	
<b>Tire Size</b>		<b>400/60-15.5</b>	
<b>Tractor Requirements</b>		<b>134 kw, 180 hp</b>	
<b>Hydraulic Remotes</b>		<b>3 pair (4 pair with marker option)</b>	
<b>Monitor</b>		<b>RDS R-tronic</b>	
<b>Tramlines</b>		<b>2+2 or 1+1 shutoff</b>	
<b>Opener Travel</b>		<b>20 cm (10 cm up, 10 cm down)</b>	
<b>Opener Depth</b>		<b>0-9 cm</b>	
<b>Opener Down Pressure</b>		<b>0-80 kg</b>	
<b>Coulter Working Depth</b>		<b>0-15.5 cm</b>	
<b>Coulter Down Pressure</b>		<b>0-250 kg</b>	

***Note: Weights based on 7.5" (19 cm) row spacing and will vary depending on options. Transport clearance will vary depending on tractor.***

**[Top of Page](#)**