

3600

TWIN-LINE® PLANTER

For season after season of reliable service, the Kinze 3600 Twin-Line Planter gives you the perfect combination of toughness and functionality. This versatile 12 and 16 row planter comes with standard features and options to meet the demands of any planting operation.



3600 Twin Line® 16" Row N (30") with Interplant® package and row-unit mounted no-till coulters.

THE KINZE FRAME - The backbone of the 3600.

The three-section frame features 7° of up and down flex, allowing the frame to flex naturally in fields with rolling terrain and terraces. And with the lift and rotate system, you can get from the field to the road in no time.

FERTILIZER OPTIONS

Increase the efficiency of your operation by utilizing the liquid fertilizer packages on the 3600 Twin-Line planter, available with total capacity of 600 gallons (four 150 gallon tanks). Liquid fertilizer piston pump packages include CDS-John Blue® heavy duty squeeze pumps (requires two pumps) or CDS-John Blue® piston pumps, flow dividers and ground drive system. Or select our dry fertilizer package with a total capacity of 3,300 – 4,400 lbs. depending on your row configuration.

Fertilizer openers are available for use with any tillage system. Choose from heavy duty, notched single disc or double disc fertilizer openers. If more depth control is needed, you can add optional notched single disc opener depth/gauge wheels.

INTERPLANT®

Eliminate the congestion of side-by-side units and bring added efficiency to your operation with Interplant row units. Interplant provides the 3600 with 15" spacing (except on the 3600 12 row wide model which has 36"-38" row spacing and 18"-19" Interplant row spacing.) An even-row push unit is also available to outfit your planter for the way you farm.

KINZE EDGEVAC®

- The leading edge in vacuum seed metering.
- Excellent seed spacing and population control.
- Consistent seed drop from the edge.
- Less tumbling action or ricochet effect inside seed tube.
- Fewer moving parts, less service and maintenance.
- Self-adjusts to maintain the vacuum seal.



SEED MONITORS

Seed monitor options for every operation.

Kinze Vision® – One display. Touch screen control. Available with auto-swath control, variable rate seed control, integrated planter monitor functions and mapping with GPS.



Kinze Cobalt™ – Save time and reduce guesswork. Available with manual swath control, variable-rate seed control, and integrates with radar ground speed sensors. Easy upgrade to Vision® display.

KPM III – Available in both magnetic and radar distance sensor options, a single LCD monitor to display seed count and alphanumeric planting data – including speed, row spacing, seed spacing and seed population.

3600

TWIN-LINE® PLANTER

SPECIFICATION

Number of Rows	12	12	12	16	16
Row Spacing	30"	30"	36"-38"	30"	30"
Tongue Style	Y	T	Y	Y	T
Weight Empty (Mechanical)	12,780 lb.	12,780 lb.	13,522 lb.	15,730 lb.	15,730 lb.
Weight Empty (EdgeVac)	13,185 lb.	13,185 lb.	----	16,210 lb.	----
Transport Height	10' 8"	10' 8"	10' 8"	11' 0"	11' 0"
Operation Length	21' 0"	21' 0"	22' 0"	24' 0"	24' 0"
Transport Length	36' 10"	36' 10"	45' 10"	46' 10"	46' 10"
Operation Width	31' 2"	31' 2"	37' 2"	41' 2"	41' 2"
Transport Width	11' 2"	11' 2"	13' 4"	11' 2"	11' 2"



KEY FEATURES

- **Three-Section Double Frame** – with a four row center section and four rows on the wings on 12 row units and six on the wings on 16 row units.
- **Frame Flexibility** – equipped with heavy-duty wing hinges and capable of 7° up and down movement.
- **Hydraulically Operated, Over-Center Wing Locks** – allow the wings to flex while planting and rigidly lock for transport.
- **Low-Profile, Two-Fold Row Markers** – equipped with 16" diameter solid marker blades. Keeps transportation heights under 11 feet.
- **Twin-Line® Transport System** – features a 7" x 7" stainless steel-clad center post with eight UHMW plastic pads that glide against the post as it's raised and lowered – this means no lubrication and no maintenance.
- **Half-Width Planting** – shut off either side of the planter with 12VDC point row clutches, activated from the cab-installed control console.
- **Excellent Stability and Load Carrying Capacity** – four custom-molded, radial transport tires (used in the field and during transport), 8-bolt wheels and oversized hubs are spaced to match the duals on the tractor.
- **Complete Electric/Hydraulic Control** – row markers, point row clutches and the folding/unfolding functions are all controlled from the seat of your tractor.

MORE OPTIONS

- Electronic Seed Monitors/Displays (KPM III, Cobalt™ and Vision®)
- Air Clutch Package (Requires Air Compressor Package)
- Hydraulic Drive Package
- Solid Row Interplant® Packages
- Even Row Interplant® Push Row Unit Packages
- Interplant® Air Clutches
- Interplant® Monitor Packages
- Rubber V Closing Wheels
- Cast Iron Closing Wheels
- Quick-Adjustable Down Force Springs
- Pneumatic Down Pressure (Requires Air Compressor Package)
- Liquid Fertilizer Packages
 - Four 150 gallon tanks with lids
 - Liquid Fertilizer Openers
 - Liquid Fertilizer Pumps
- Dry Fertilizer Packages
 - Double Disc, Notched Single Disc and HD Single Disc Fertilizer Opener Packages
- Rear Trailer Hitch (for use with Liquid Fertilizer Piston Pump Option only)
- Half Rate (2 to 1) Drive Reduction Packages
- Rock Guard Packages (transport wheel arms)
- Auxiliary Work Light Packages



Kinze Manufacturing, Inc.
1-800 at Exit 216 • Williamsburg, Iowa • 52361-0806 USA
www.KINZE.com