

# The Toughest Cutter In Its Class!



**RCR18 SERIES**

60" 72"



## Land Pride's **New** RCR18 Series Rotary Cutter

These RCR18 Series Rotary Cutters are built and designed by Land Pride for cutting on gently sloping or slightly contoured right-of-ways, pastures, around the farm or around town.

Their 60" cutting width on the RCR1860 and the 72" cut on the RCR1872 makes them compatible with the more maneuverable and lower horsepower tractors in the 20hp to 50hp output ranges. These RCR18 Series Rotary Cutters utilize 540rpm PTO, Category 1, 3-point attachment, and are Quick-Hitch adaptable. Both units offer a laminated or a solid rubber trailing caster wheel. Customers may choose shear bolt or slip-clutch protection on the standard ASAE Category 3 driveline.

These RCR18 Series Cutters clear grass, weeds, and light brush up to 1" in diameter. The RCR1860 has a cutting height range of 1-1/2" to 13" and the

RCR1872 has a cutting height range of 1-1/2" to 11-1/2". The cutting blade tip speed for the RCR1860 is 16,363 fpm while the RCR1872 has a tip speed of 14,955 fpm. These units come with a standard 10 ga.

standard-duty stump jumper and welded on full length skid shoes. The 24" stump jumper protects the drive train from ground

obstructions. Metal band shielding is standard on the rear and optional rubber deflectors or chain guard selections are available for front or rear guarding.

- 20 - 50 HP
- All Welded Deck for Superior Quality
- Clevis Hitch for Easy Hook-up
- 3-1/2" Wide Front to Rear Support Channels
- Rear Metal Band to Contain Debris
- 2 Year Limited Gearbox Warranty\*

# RCR18 Series Rotary Cutter Specifications

Model	RCR1860	RCR1872
Cutting Width	60"	72"
Overall Width	65"	77"
Overall Length	97"	110"
Blade Tip Speed	16,363 fpm	14,955 fpm
Machine Weight	585 lbs.	711 lbs.
Drive Shaft	ASAE Category 3 Shear Bolt or Slip Clutch	
Recommended Tractor PTO HP	20-50 HP	
PTO Speed	540 rpm	
Gearbox	Cast Iron Housing Beveled Gears	Cast Iron Housing Beveled Gears
Cutting Height	1 1/2" - 13"	1 1/2" to 11 1/2"
Deck Material Thickness	11 Ga. (.120")	10 Ga. (.134")
Side Skirt Construction	11 Ga.	10 Ga.
Deck Height (Bottom of Deck to Bottom of Skid Shoe)	7 1/2"	9"
Skid Shoe Construction	Full length welded on	
Tailwheel Mount Assembly	Welded A-arm and Caster Fork	
Tailwheel	4" x 8" x 15" Laminated Tire or 4" x 16" Solid Rubber	
Hitch	Category I Quick Hitch Adaptable	
Blade Holder	Round Pan 10 ga. x 24" (Stump Jumper)	
Blades	1/2" x 3" Heat Treated Alloy Steel Free-Swinging High Lift; Low Friction	
Blade Cutting Capacity	1" Diameter	
Front Guard**	Optional Rubber Belting	
Rear Guard**	Optional Rubber Belting	

- Laminated or Solid Rubber Tailwheel
- Optional Front and Rear Rubber Guards\*\*
- Deep Deck Construction to Handle Heavy Conditions
- Floating Top Link for Level Cutting in Undulating Terrain
- Floating Top Link Works with Land Pride Quick Hitch
- Driveline Storage Hook



PO Box 5060 • Salina, KS 67402-5060  
Visit our Dealer Locator at [www.landpride.com](http://www.landpride.com)

\* See your dealer for complete warranty information.

\*\* Chain guarding available through Land Pride Parts Department.