

TONDEUSE SERIE **ZXT** MOTEUR DE 24 HP À 31 HP  
TONDEUSE DE 54" & 60"



# ZXT PRO

54" 60"

The ZXT PRO from Land Pride compliments our Zero Turn Mower line-up with commercial duty features, yet priced right and sized right to fit both high-end residential and commercial class users.



### Striping Roller

An optional striping roller is available to give your cut grass that "ball field" look. The kit easily attaches to the rear of the cutting deck.



## OUTSTANDING FEATURES

### Floating Front Axle

Lock or unlock the floating front axle to match the conditions you are in. The floating feature allows all 4 wheels to be in contact with the ground at all times, ensuring a comfortable, secure ride. The rigid axle position allows you to hang the deck over the curb for close trimming. Easily lock and unlock the axle with the flip of a lever located under the floorpan.

### Two Independent Hydraulic Reservoirs

The main tubular frame is used as the reservoir for the hydraulic system. By separating this into two independent hydraulic reservoirs, only half the system needs to be flushed if contaminants are present; saves you time and money! By dissipating the heat over a wider area, the hydraulic oil is able to run at cooler temperatures.

**2 YEAR**  
Limited  
Warranty\*

The segmented roller allows each segment to continue to roll during turns, versus skidding.



[www.landpride.com](http://www.landpride.com)



### Overall Comfort

If you mow for a living, or just a few hours a week, you want to be as comfortable as possible. You can match our selection of seats to match your physique, and they have adjustments to match your height as well. Our Deluxe seat with suspension springs gives you nice protection against a bumpy yard, and the Adjustable Suspension seat allows you to dial in the type of suspension that matches the area you are mowing.

### Durability

Top quality components are used to ensure that your ZXT Pro mower gives you years of productive, efficient and safe use. We've tested this mower in tougher than normal conditions, and have also made sure that it meets all ANSI safety tests throughout the design period.



## ZXT Series

<b>Cutting Width</b>	54" or 60"
<b>Cutting Height</b>	1"-5" in 1/4" increments
<b>Engine</b>	25 HP & 31 HP Kawasaki or 24 HP Honda or 26 HP Briggs & Stratton
<b>Deck Thickness</b>	10 Gauge Decks w/11 ga. Doublers Plate & 3/16" reinforcement plate connecting spindle housing mounts
<b>Steering</b>	Twin Lever
<b>Anti-Scalp Rollers</b>	4
<b>Blades</b>	Heat Treated, High Lift, Fusion technology
<b>Pivoting Front Axle</b>	Locked or Unlocked
<b>Blade Belt</b>	Single V-Belt
<b>Blade Spindles</b>	1 3/8" Spindle, Cast Iron Housing, Greaseable Ball Bearings
<b>Tires</b>	Front: 13 x 5 - 6, Rib Tread; Rear: 24 x 10.5 - 12, Turf Tread
<b>Fuel Capacity</b>	12 U.S. Gallons
<b>Hydraulic Oil Capacity</b>	4 U.S. Gallons
<b>Pumps</b>	2, 1 per Rear Wheel Drive Motor
<b>Pump Drive</b>	V-Belt from Engine Crankshaft
<b>Wheel Drive</b>	Direct Drive, High-Torque
<b>Parking Brake</b>	Internal Wet Disc Brakes, Manually Activated
<b>Ground Speed</b>	Forward 0-11 mph; Reverse 0-5.5 mph
<b>Seat</b>	Deluxe seat w/wo suspension springs or suspension adjustment seat

[www.landpride.com](http://www.landpride.com)

# ZXT Pro

54" 60"  
[continued]



- \* 2 Year Warranty**
- ★ Overall Unit - 2 years
  - ★ Engine - 2 years
  - ★ Mower Deck - Lifetime on front edge
  - ★ Frame - Lifetime against breakage
  - ★ Blade Spindle - 3 years
  - ★ Gauge Wheel Yoke Bearings - 3 years



**Front Caster Wheels**  
Two front mounted 13 x 5 ribbed tread caster wheels mounted in heavy-duty swivelling forks for quick and durable response.



Front edge of deck is reinforced with a heavy underside box section.

The Land Pride ZXT Pro Zero Turn Mower has mowing applications from farms to large estates and school campuses to industrial parks. These mowers are designed to meet the cost conscious needs of customers who are looking for the increased productivity and reliability of a commercial grade mower.

The 54" and 60" cutting decks, high quality dual hydrostatic drive system components, proven performance engine offerings, incredibly strong frame construction, independent and isolated hydraulic reservoirs, floating front axle, and comfortable seating selections make the ZXT Pro Series a Zero Turn Mower that both high-end residential and commercial class customers will truly appreciate.



[www.landpride.com](http://www.landpride.com)

# SUPERIOR CONSTRUCTION

**One Tough Deck...**  
The ZXT deck is constructed of 10 gauge steel, with an additional 11 gauge steel plate, and 3/16" plate surrounding the blade spindle housings. The additional 1/2" trim side rib offers strength curbs or tree stumps cannot match. The pliable, rubber discharge chute rapidly springs back into shape when hit by an obstruction.

**...And a Frame to Match**  
The ZXT frame follows in the same path as our commercial rated ZTi model; a tubular frame that also acts as two independent hydraulic reservoirs. The thick wall tubing runs the length of the mower, and provides a hefty support for the overall unit.

**Deck Height Adjustment**  
The spring assisted deck height adjustment is easily changed with the push of the foot pedal. Change cutting heights in 1/4" increments to get just the right appearance to your lawn.

**Operator Safety**  
A manually activated over-center lever next to the operator's seat easily and conveniently activates or releases the enclosed disc park brake. Rising from the seat with the blades engaged will cut engine power and stop blade rotation. The engine cannot be started with the blade switch in the "on" position.

**Stability**  
The 49" outside tire width and 24 x 10.5 rear tires provide excellent stability and maneuverability over uneven and hilly ground, while also providing good trim capability.



[www.landpride.com](http://www.landpride.com)

# ZXT Pro™ Commercial Series



Pivoting Front Axle

Cutting Width: 54" or 60"  
 Cutting Height: 1"-5" in 1/4" increments  
 Length: 83"  
 Overall Width with Discharge Chute Up:  
 54: 55<sup>3</sup>/<sub>8</sub>"; 60: 61<sup>3</sup>/<sub>4</sub>"  
 Tire to Tire Width: 49"  
 Deck Thickness: 10 Gauge with 11 Gauge  
 doubler plate & reinforcement rings  
 around spindle housing mounts  
 Steering: Hydrostatic Twin Lever

Anti-Scalp Rollers: 4  
 Certified Folding ROPS  
 Seat Belt  
 Blades: Heat Treated, High Lift, Fusion® edge  
 54: .25 x 2.5 x 18.8; 60: .25 x 2.5 x 20.9  
 Blade Tip Speed: 54: 18,515 fpm; 60: 18,700 fpm  
 Blade Belt: Single B-section V-Belt w/spring tensioner  
 Blade Spindles: 1 3/8" Ductile Cast Iron Housing,  
 Greaseable Ball Bearings  
 Front Tires: 13 x 5 - 6, Rib Tread  
 Rear Drive Tires: **23x10.5-12**  
 Engine: Cylinders: 2  
 Cooling: Air Cooled  
 Ignition: Electronic  
 Hourmeter: Engine runtime  
 Fuel: Unleaded Gasoline  
 Fuel Capacity: 12 U.S. Gallons  
 Drive System - Dual Hydrostatic  
 Hydraulic Reservoirs- two independent & isolated  
 7.5 pint capacity each frame reservoir  
 Drive: V-Belt from Engine Crankshaft  
 Wheel Drive: Hi-torque piston type planetary reduction motors  
 Parking Brake: Over-center console lever to enclosed wet disc  
 Ground Speed: Forward 0-11 mph; Reverse 0-5.5 mph  
 Seat: Deluxe Cushion Seat w/Armrests  
 Cup Holders: 2

**ALL MOWERS ARE RED IN COLOR**

<b>MODEL NUMBER</b>	<b>DESCRIPTION</b>	<b>APPROX. MACHINE WEIGHT</b>	<b>SHIPPING WEIGHT</b>
<b>ZXT54-022691</b>	<b>ZXT PRO SERIES, 54" Deck</b> 26 HP Briggs ELS w/Deluxe Cushion Seat w/Armrests, Folding ROPS	<b>1,141#</b>	1,331#
<b>ZXT54-022591</b>	<b>ZXT PRO SERIES, 54" Deck</b> 25 HP Kawasaki w/Deluxe Cushion Seat w/Armrests, Folding ROPS	1,141#	1,331#
<b>ZXT54-022491</b>	<b>ZXT PRO SERIES, 54" Deck</b> 24 HP Honda w/Deluxe Cushion Seat w/Armrests, Folding ROPS	1,141#	1,331#
<b>ZXT54-023191</b>	<b>ZXT PRO SERIES, 54" Deck</b> 31 HP Kawasaki: Air Cooled Engine, Deluxe Cushion Seat w/Armrests, Folding ROPS	1,141#	1,331#
<b>ZXT60-022691</b>	<b>ZXT PRO SERIES, 60" Deck</b> 26 HP Briggs ELS w/Deluxe Cushion Seat w/Armrests, Folding ROPS	<b>1,159#</b>	1,349#
<b>ZXT60-022591</b>	<b>ZXT PRO SERIES, 60" Deck</b> 25 HP Kawasaki w/Deluxe Cushion Seat w/Armrests, Folding ROPS	1,159#	1,349#
<b>ZXT60-022491</b>	<b>ZXT PRO SERIES, 60" Deck</b> 24 HP Honda w/Deluxe Cushion Seat w/Armrests, Folding ROPS	1,159#	1,349#
<b>ZXT60-023191</b>	<b>ZXT PRO SERIES, 60" Deck</b> 31 HP Kawasaki: Air Cooled Engine, Deluxe Cushion Seat w/Armrests, Folding ROPS	1,159#	1,349#
<b>ADD OPTION NO</b>	<b>YOU MAY CHOOSE AN ALTERNATE SEAT</b>		
<b>-03</b>	Molded Vinyl Seat with Comfort Suspension Adjustments (Delete Option -02)	35#	35#
<b>-04</b>	Deluxe Cushion Seat w/Armrests and Springs (Delete Option -02)	20#	20#

### ZXT Pro (Engine Specifications)

Mower Model No	ZXT54 & ZXT60			
Engine Manufacture	Honda	Kawasaki		Briggs & Stratton
Horsepower	24	25	31	26
Engine Model Type	GXV670-TAF	FH721V	FX850V	44P777-0116-E1
Max Torque	37 FT. LBS @ 2500 RPM	41.2 FT. LBS @ 2400 RPM	54.3 FT. LBS @ 2400 RPM	N/A
Charging System	12-volt, 20 amp	12-volt, 13 amp	12-volt, 15 amp	12-volt, 16 amp
Starter	12-volt solenoid shift positive engagement	12-volt Electric starter	12-volt Electric starter	12-volt Industrial Starter
Ignition	Keyed 12 volt electronic system			
Governor	Mechanical			
Fuel Type	Unleaded gasoline with octane rating of 87 or higher			
Oil Cooling	External Cooler	N/A	External Cooler	N/A
Engine Cooling	Air cooled, Fly-wheel fan			
Engine Type	4-stroke OHV, V-twin cylinder, gasoline			
No of Cylinders	2			
Displacement	40.9 cu. in. (670cc)	41.2 cu. in. (675cc)	52 cu. in. (852cc)	44.2 cu. in. (725cc)
Compression Ratio	8.3:1	8.1:1	8.2:1	N/A
Spark Plug No.	ZGR5A (NGK) J16CR-U (DENSO)	BPR4ES (NGK)		
Oil Capacity with Filter Change	2.6 US quarts	2 US quarts	2.1 US quarts	2 US quarts
Oil Type	SAE 10W-30			
Oil Filter Part No.	831-038C	831-034C		831-053C
Fuel Filter Part No.	831-035C	831-031C		831-035C
Air Filter Part No.	Inner Filter	839-374C	839-973C	None
	Outer Filter	839-323C	839-974C	831-054C

### ZXT Pro (Hydrostatic Transmission Specifications)

Mower Model No	ZXT54	ZXT60
Traction Drive Type	Dual Hydrostatic Transmission	
Hydraulic Motor/Pumps	Two variable displacement, axial piston type.	
Hydraulic Motor/Pump Drive	V-belt drive from engine crankshaft	
Hydraulic Oil Type	SAE 20W-50 engine oil	
Hydraulic Reservoirs	Dual independent tubular chassis construction with expansion tanks for oil level check.	
Hydraulic Oil Capacity	7.5 pints oil capacity each side or 15 pints total	
Hydraulic Oil Filter No.	810-590C	

### ZXT Pro (General Specifications)

Mower Model No	ZXT54	ZXT60
Certifications and Standards	Complies with ANSI B71.4 testing and safety standards for commercial riding mowers.	
Weight with deluxe seat	1084 lbs.	1109 lbs.
Width of Cut	54"	60"
Cutting Height	1" to 5" in 1/4" increments	
Trim Capacity (left side)	4"	10"

## ZXT Pro (General Specifications)

Mower Model No	ZXT54	ZXT60
Overall width	69 1/8"	75 1/8"
Chute down		
Chute up	62 1/4"	68 1/4"
Overall Length without hitch plate	83 1/2"	
Tire-to-tire width:	49"	
Overall Height	56 1/2" to top of folded ROPS and 70 1/2" to top of unfolded ROPS	
Certified ROPS	Standard with S/N 636305 and higher.	
Drive Tires	23 x 10.5 - 12 Turf Tread	
Front Tires	13 x 5 - 6, Ribbed tread with roller bearings	
Hour Meter	Standard equipment	
Fuel Capacities	12 US GAL	
Steering Type	Hydrostatic Twin lever steering provides independent control of each drive wheel.	
Twin Lever Steering Controls	Speed, forward, reverse, brake, and turns.	
Steering Turning Radius	True zero degree. Turns with counter-rotating independent drive wheels.	
Brake Service	Hydrostatic dynamic braking.	
Park Brake Type	Manual activated over-center lever to wet disc brake.	
Ground Speed	Forward: 0-11 MPH Reverse: 0-5.5 MPH	
Motor Drive	Single V-belt with electric clutch and spring tension idler pulley.	
Wheel Drive	High torque piston type planetary reduction motors	
Safety Features	Electric logic-control system governs blade engagement, forward & reverse motion, engine starting & running, and parking brake functions.	
Seat Options	Deluxe cushion seat with arm rests or molded vinyl comfort suspension seat with arm rest.	
Mainframe Construction	Welded steel	
Drive Motor Mount	Fabricated from 3/16" steel plate.	
Front Caster Wheels	Free turning with greasable roller bearings.	
Front Caster Forks	5/16" steel.	
Deck Thickness	10 Gauge deck with 11 gauge doubler plate and 1/4" reinforcement plate at spindle housing mounts	
Box-Section Reinforced Front Edge	11 ga. thick	
Deck Trim Edges	Solid 1" x 3/8" steel bars for reinforced impact area	
Deck Housing Depth	5 1/8" deep, (room for high-capacity mowing)	
Deck Lift	Foot-operated deck height adjustment with locking pin for setting height.	
Hand Operated Controls	Ignition switch, throttle lever, control levers, park brake, blade engagement switch, choke knob and Fuel Tank Selector Valve.	
Indicators	Engine warning light and hour meter for engine run time.	
Cup Holder	Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size.	
Cutting Height Adjustments	Height adjustment in 1/4" increments from 1" to 5".	
Mowing Blades	3 Heavy-duty, heat-treated, high-lift steel blades	
	.25" x 2 1/2" x 18.8"	.25" x 2 1/2" x 20.9"
Blade Tip Speed	18,515 FPM	18,700 FPM
Blade Drive	Single B-Section belt drive to all three spindles. Spring tension idler pulleys.	
Blade Spindles	Machined ductile iron housing, 1 3/8" diameter high carbon steel shafts and greasable ball bearings.	
Deck Suspension	Four point suspension from frame by mechanical linkage with counter balance springs.	
Anti-Scalp Rollers	4 Anti-scalp rollers to improve flotation in rolling and uneven terrain.	

## ZXT54 & ZXT60 Series

Features	Benefits
<b>54 or 60" Cutting width</b>	Sized right and priced right for high-end residential and cost conscious ranchers, farmers, estate owners, and commercial operators.
<b>1" to 5" Cutting height</b>	Cutting height in 1/4" increments for good cutting height range control.
<b>49" Outside drive tire stance</b>	Provides excellent stability over uneven and hilly ground along with good maneuverability.
<b>High Ground speed</b>	Forward 11 mph and reverse 5.5 mph for high productivity.
<b>Adjustable steering levers with comfort grip handles</b>	Wide range of adjustments to accommodate almost any size of operator. Grips are designed for operator comfort and sustained productivity.
<b>Stronger clean frame design</b>	Integral frame and hydraulic reservoir construction reduces component clutter under the seat for easy cleanout and service access.
<b>Single welded 10 gauge deck frame with reinforced edges</b>	Makes a stronger deck and reduces unwanted flex.
<b>Rapid deck height adjustment</b>	The foot operated with spring assist deck lift and deck stop locator makes for a quick and easy precise cutting height adjustments.
<b>Easy clean-out deck top</b>	Deck allows air and debris move across the top for improved belt cooling and easy clean out.
<b>Excellent trim capability</b>	49" wheel stance provides for good trim capability especially when equipped with a 60" deck.
<b>Mid-mount deck design</b>	Puts deck closer to operator's line of sight for more efficient and precise operation.
<b>Floating deck design</b>	Chain suspension design provides excellent flotation over uneven terrain.
<b>Four anti-scalp rollers</b>	Two located on deck ends and two located toward mid-decks keeps scalping to a minimum.
<b>Completely independent twin hydrostatic drives</b>	Outboard heavy-wall tubular frame members also serve as independent left and right side hydraulic reservoirs for hydrostatic drive motors and fan cooled hydrostatic pumps located on each side of the machine eliminating the possibility of cross-contamination.
<b>Premium wide stance drive tires</b>	Provide excellent traction, outstanding side-hill stability and a smooth ride. (23x10.5-12)
<b>Front ribbed tires mounted in heavy duty pivoting caster forks</b>	Provide for a quick and durable turning response. (13 x 5-6 ribbed tires).
<b>Lockable floating front axle.</b>	Floating front axle provides for smoother ride, more uniform cut, and optimal traction capability by keeping all tires equally in contact with the ground over uneven terrain. Axle lock provides for temporary curb or edge cutting without grounding or hanging up the deck.
<b>Electric clutch control</b>	Provides an easy smooth engagement of the mower blade drive system.
<b>Kevlar drive belts</b>	Drive belts made with Kevlar™ fiber provide long belt life. One hydrostatic pump drive belt and one deck drive belt is easier to maintain and not as expensive as multiple belt designs.
<b>1 3/8" blade spindles mounted in ductile iron housings</b>	Blade spindles and spindle housings are designed to handle heavy shock loads.
<b>Accessible blade spindle zerks</b>	Makes greasing the blade spindles easy.
<b>Heavy duty heat treated Fusion® high lift blades</b>	Made from highest quality .25" thick fusion treated steel for high wear and increase blade life. High lift design stands grass up before cutting.
<b>High blade tip speed</b>	18,515 fpm on the 54" deck and 18,700 fpm on the 60" deck for clean quality of cut.
<b>Choice of engines</b>	Proven 26 hp Briggs and Stratton ELS, 25 hp Kawasaki, 31 hp Kawasaki, or 24 hp Honda engines to meet customer preferences with power and performance to spare.
<b>Electric start with choke control</b>	Keyed ignition and manual choke control are placed for one-handed starting convenience.
<b>Engine oriented for easy access</b>	Easy access to oil dipstick, spark plugs, oil drain ports, air filters and oil filters for convenient serviceability.
<b>Center mounted rear engine placement</b>	Provides maximum mower stability, easy service access, increased leg room, and increased air flow around engine fins to extend engine life.
<b>Engine air filtration</b>	Premium Honda and Kawasaki engines come standard with a remote air intake which filters out 95 percent of airborne particles. The Briggs ELS comes standard with a proven 2-stage quick access filter cartridge.
<b>Isolated exhaust muffler</b>	Muffler is hidden and tucked down under to reduce noise and provide protection against burns

## ZXT54 & ZXT60 Series

<b>Ergonomically designed control console</b>	Instrumentation and console controls are positioned for easy visual or fingertip access.
<b>Hour meter</b>	Measure actual engine run time to monitor service intervals.
<b>Sleek styling twin six gallon fuel tanks with extra large fuel caps and selector valve</b>	12 Gallon fuel capacity for plenty of operating range and decreased down time. Extra large fuel openings for easy fueling. Fuel caps are vented, placed inboard and center mounted to protect caps from damage and prevent overflow spills on inclines.
<b>Fuel selector/shutoff valve</b>	Provides on the go switching from one tank to another and shutoff for servicing and storage.
<b>Molded-in dual cup holders and storage compartments</b>	Tanks are molded with cup holders that fit a wide variety of cups and are in easy access to the driver. A storage compartment molded next to the cups offer additional operator convenience.
<b>Lever activated park brake</b>	A manually activated over-center lever next to the operator's seat easily and conveniently activates or releases a highly durable and reliable enclosed wet disc brake. Mower will not move until brake is released.
<b>Hinged seat platform</b>	Provides easy service access without tools.
<b>Comfortable adjustable seat</b>	Deluxe Cushion with/without spring suspension or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity.
<b>Seat safety interlocks</b>	Rising off of the seat with blades engaged will cut engine power and stop blade rotation. Engine cannot be started with blade engagement switch in "on" position.
<b>Hinged floor platform</b>	Provides quick and convenient service access to topside deck components without tools.
<b>Certified ROPS</b>	Certified folding ROPS for added operator protection.
<b>Sun Canopy</b>	An optional folding soft sun canopy is available to fit fixed or folding ROPS.
<b>Snow Plow</b>	An optional 60" or 72" motion activated snow plow is available for snow removal and year round usage. Mower deck does not need to be removed to attach the snow plow.