

Precise metering and seed-to-soil contact.

PS15 SERIES

Cat. 1 — 6'



- Cat. 1 Hitch, Quick-Hitch adaptable
- Lower hitch-clevises for easy hook-up
- 72" Seeding width
- #40 Chain with spring loaded idler
- Powder metal flutes in the seed cups help dissipate heat
- Tire track removers for consistent seed emergence across entire width
- Heavy-duty lid with seed splash guard
- Ground driven metering for constant seeding
- Water tight seedbox with agitator to eliminate seed bridging
- Wind guarded seed drop keeps seeds falling at same rate to the ground
- Lift hooks for easy loading - just right to take from site to site



"Precision seeding" is accomplished using proven fluted metering cups. Each flute grabs just the right amount of seed for even distribution. Millions of cups are in use for a variety of crops around the world.



(Cover removed for photo.)

Various seeding rates can be obtained by turning the dual sprocket over. The easy drive system assures a consistent flow of seed. The rear roller is spring loaded to stay in constant contact with the ground. The steel "bumper" protects the drive system against impacts.



The rear roller is spring loaded to keep in constant contact with the ground, promoting healthy "seed-to-soil" contact.



All welded box with seed splash guard and paddle style agitator.

Primary Seeders

PS1548 & PS1572 Primary Seeders		
	PS1548	PS1572
Width	55"	72"
Seeding Width (Broadcast)	51"	70 1/2"
Weight (Approximate Pounds)	870#	1165#
Seed Capacity	1 Bushel/Foot (4 bushel)	1 Bushel/Foot (6 bushel)
Feeder Cup Drive (Roller Drive)	Chain Driven from right side of front roller with paddle type agitator above seed cups	Chain Driven from right side of front roller with paddle type agitator above seed cups
Track Removers	Double torsion spring height adjustable and replaceable One each	Double torsion spring height adjustable and replaceable Two each
Bed Forming Rollers - Front	12" OD notched, cast iron, 20 each with free floating mounting tube and 1 1/2" sealed greaseable bearings	12" OD notched, cast iron, 29 each with free floating mounting tube and 1 1/2" sealed greaseable bearings
Bed Forming Rollers - Rear	9 1/2" OD notched, cast iron, 21 each with free floating mounting tube and 1" greaseable bearing mounted on pivoting spring loaded arms	9 1/2" OD notched, cast iron, 28 each with free floating mounting tube and 1" greaseable bearing mounted on pivoting spring loaded arms
Hitch	Category I, Offset to right 8 5/8"	Category I