



CUTTERS

25 Series
8' & 10'
Rotary
Cutters



RCR2596 & RCR2510

30-110 HP

5 Year
Limited
Gearbox
Warranty

Land Pride's **New** 25 Series 8' and 10' Rotary Cutters

Land Pride's RCR25 Series 8' and 10' Rotary Cutters are suited just perfect for those medium sized chores. Designed for excellent performance in pastures, set aside acres, roadsides and routine farm maintenance, we have a model to fit your 30-110 HP tractor. Both sizes are available in a 3-Point or Pull-Type model. Standard with two stumpjumpers, each with two free swinging heat-treated blades, these cutters are designed to cut grass, weeds and saplings up to 1" in diameter. Front and rear guarding must be selected, and are available in rubber or chain. 15¹/₄" Laminated tires are standard on the 3-point model, while the pull-type offers a selection of 24" aircraft tires, 15" wheel rims or 21" laminated tires.

Pull-type - The Pull-type model features two leveling rods that connect the rear axle to the front tongue. This enables the deck to stay level during uneven ground conditions. The height controlling axle cylinder is attached to two deck springs which help cushion the cutter in rough terrain.

3-Point - The 3-point unit utilizes two casting laminated tailwheels for smooth, trouble-free performance. The easy to attach clevis hitch is designed to fit Cat. 1 or 2 tractors on the 96" model, and Cat. 2 or 3 tractors on the 10' model.

Sturdy Deck Design - The all-welded, 10 ga. deck features side to side, and front to rear channels for overall support.



RCR25 Series Specifications

Model	RCR2596	RCR2510, RCRM2510
Hitch	Lift-Type - Category 1 & 2; Quick-Hitch Adaptable, Pull-Type - w/Dual Leveling Rods	Lift-Type - Category 2 & 3; Quick-Hitch Adaptable, Pull-Type - w/Dual Leveling Rods
Working Width	7'10"	9'10"
Overall Width	8'2"	10'3"
Overall Length	Lift - 8'11", Trail - 11'3"	Lift - 9'2", Trail - 12'1"
Cutter Weight <i>(w/o chain or rubber shield)</i>	Lift-Type 1,238 lbs. Pull-Type 1,523 lbs.	Lift-Type 1,575 lbs. Pull-Type 1,860 lbs.
Blade Tip Speed	540 RPM: 14,492 fpm	540 RPM: 17,749 fpm; 1000 RPM: 18,035 fpm
Deck Material Thickness	10 Gauge	
Gearbox Rating	Center - 120 HP; Outboard - 60 HP	
HP Rating (PTO)	Lift-Type - 50-110 HP; Pull - 30-110 HP	Lift-Type - 60-110 HP; Pull - 50-110 HP
Cutting Height	2" - 12"	
Cutting Capacity	1"	
Safety Shields (optional)	Front & Rear Chain / Front & Rear Rubber	
Skids	Replaceable	
Deck Height	9 ⁵ / ₈ "	
Blades	1/2" x 4" Heat-Treated; Free-Swinging Suction Blades	
Stump Jumper	Round Pan ³ / ₁₆ "	
Driveline	Cat. 4 w/Equal Angle U-Joint on Pull-type	Cat. 4 w/Equal Angle U-Joint or Constant Velocity U-Joint
Driveline Safety Protection	540 rpm - 4 Plate Slip-Clutch 1000 rpm - 2 Plate Slip-Clutch	
Gearbox <i>(Speed up Beveled Gears)</i>	540 rpm PTO Driven Gearbox Cat Iron Housing, Beveled Gears	540 rpm or 1000 rpm PTO Driven Gearbox Cat Iron Housing, Beveled Gears
Tailwheel	Lift-Type: 2 each, 4" x 8" x 15 ¹ / ₄ " Laminated Pull-Type: 2 each, 6" x 9" x 21" Laminated or 24" Aircraft Tires or 15" Automotive Rims	



- 3-Point or Pull-Type
- Clevis Hitch on 3-Point
- Narrow Tongue on Pull-Type
- Stumpjumpers are Standard
- Choice of Tires
- Red, Green or Buckskin Colors
- High Blade Tip Speed
- All-Welded Deck



Front and rear guarding is highly recommended in any application. Please be sure you understand how your Rotary Cutter is equipped upon purchase. All Land Pride Rotary Cutters are tested and pass rigorous voluntary testing requirements as specified by ANSI, ASAE and SAE.



PO Box 5060 • Salina, KS 67402-5060
Visit our Dealer Locator at www.landpride.com
LP_NPB_RCR25 3/25/05