

SPECIFICATION TÊTE 15-10-2003

Model	Optimum tree size	Recommended rotator	Recommended Foresteri crane	Maximum lift torque	Maximum Slewing torque	Base machine weight	Min. power Engine	Minimum Oil flow	Pressure	Volts
355RH	25cm 10"	FR15	H560 / H570	45kNm 33000lbft	16kNm 11800lbft	6-10 metric tons 13000- 22000 lbs.	55kW 75HP	130l/min 34GPM	210 bar 3050 PSI	24V 10A
20RH	30cm 12"	AV12 / MR10	H1195 / H1395	100kNm 73500lbft	40kNm 29500lbft	10-12 metric tons 22000-26500lbs	60kW 80HP	170l/min 45GPM	210 bar 3050 PSI	24V 10A
22RH	36cm 14"	AV12 / BBR15	H1195 / H1395	100kNm 73500lbft	40kNm 29500lbft	12-15 metric tons 26500-33000lbs	60kW 80HP	170l/min 45GPM	210 bar 3050 PSI	24V 10A
25RH	43cm 17"	AV12 / BBR15	H1195 / H1395	100kNm 73500lbft	40kNm 29500lbft	12-18 metric tons 26500- 39500lbs	80kW 105HP	200l/min 53GPM	210 bar 3050 PSI	24V 10A
30RHS	50cm 20"	BB15HD	H1680	200kNm 147000lbft	50kNm 36750lbft	20 + metric tons over 44000lbs	100kW 135HP	230l/min 60GPM	230 bar 3350PSI	24V 10A
30RH	60cm 24"	BB15HD	H1680	200kNm 147000lbft	50kNm 36759lbft	20 + metric tons over 44000lbs	120Kw 160HP	260l/min 70GPM	230 bar 3350PSI	24V 10A
410SH	30cm 12"	GV6	H560 / H570	50kNm 36750lbft	20kNm 14250lbft	7-10 metric tons 15400- 22000 lbs.	40kW 55HP	100l/min 26GPM	180 bar 2600PSI	24V 10A
560SH	43cm 17"	AV12 / BBR15	H1195 / H1395	100kNm 73500lbft	40kNm 29500lbft	12-15 metric tons 26500- 33000lbs	60KW 80HP	160l/min 42GPM	180 bar 2600PSI	24V 10A