



Home
Products
Rakes



The new Index 713T

» TerraLink

» Leaflet Index rakes



Placing two single swaths with Index 653



Raking along border lines with Index 713T



Convenient transport with the Index 713T

Vicon Index 653T-713T

Flexible solution

Exceptional versatility makes the Index 653T and 713T ideal for farmers who want to replace a single rotor rake with a big twin rotor machine. These rakes meet all your requirements, whether you need an 12.5m wide double swath to be collected by a high performance forage harvester or small night windrows for hay crops. Trailed by a drawbar linkage, the Index 653 can be hitched to small tractors from 29 kW (40 HP) onwards.



New dimension in flexibility

A new feature on the Index 713T is the possibility to sideshift both rotors - both on the front and the rear - from the tractor cab. Thanks to this patented system raking along borderline or three is no problem anymore - as the tractor will run with a safe distance to the obstacles. Additionally it is possible to drive with the tractor on already raked land.

Easy conversion from working to transport position

Index 653T and 713T are easily converted for transport position. Moving the rake to transport position only requires a simple operation of the control unit. The swath deflector will automatically fold clear. The transport width is less than 3.0 m, even with the tine arms mounted. If a more narrow swath width is required - the tine arms can easily be removed.

Maintenance free rotors

Index 653T and 713T are equipped with maintenance free compact rotor head and has 11/12 cranked tine arms on each rotor. Each rotor is fitted with tandem axles with 18 wheels for excellent ground contour followings.

50 cm lifting height

Index 653T and 713T have a lifting height of 50 cm - important on the headland and for road transportation. The rake is swung hydraulically from transport to working position and the swath deflector folds automatically. There is no need to leave the tractor seat.