

KMT 6001

## Innovative design



**The Vicon KMT 6001 with a 5.8 m working width is a real innovation in the field of high capacity mowers. It combines two mowing units: the first one, a trailed 3 m mower, is fitted with a 3-pt linkage to which the second mowing unit can be attached. Both units are equipped with a conditioner. A nylon finger rotor with an integrated wide spreading facility, allowing full width spreading of the conditioned crop.**

### Perfect ground following

Both mowing units float over ground contours independently, ensuring optimal ground following characteristics even in rough terrain. Mowing on slopes up to 38° is possible.

### Road transport

There's no need for additional transport equipment or a trailer, as the rear mowing unit can be folded hydraulically, just like a mounted mower behind a tractor. Transport dimensions do not exceed 3 m width and 4 m height limitations. This unique design results in a combination with a total weight below 3 tons, despite a working width of almost 6 m. Changing from transport to working position is done hydraulically from the tractor and only takes seconds.

### Flexible combination

An attractive solution allowing optimal use, the KMT 6001 can also be combined with an FMT 3001 front mower to achieve a working width of 8.4 m. Both mowing units remain in

their standard configuration and can also be used separately if required - with the further benefit of enhanced re-sale values for individual units at trade in time.

### Technical specifications KMT 6001

Mounting	trailed (cat.II)
Working width (cm)	580
Weight (kg)	2970
Minimum power requirement (kW/HP)	95/130
Pto speed (rpm)	1000
Swath width (cm)	(2x) 120-300
Wide spreading facility	•
Conditioner rotor with nylon fingers	•

• = standard