

## Vicon Andex 1503

### Standard specifications

#### Pro Line

4 rotor rake  
 Radial pin clutch for protection (each rotor separately)  
 Removable tine arms  
 Foldable safety guards  
 Super-C Quality tines  
 Maintenance free gear box (no greasing point)  
 Top gear running in an oil bath  
 Adjustable cam track  
 Exchangeable tine arms  
 Mechanically height adjustment, operated from the front of the rotor  
 Bi-tangential tine arms  
 Circulating hydraulic system, 1 single acting valve, 1 free return valve  
 Control box  
 Active pressure relief on front rotors  
 Passive rotor protection if hitting an obstacle  
 Braking axle  
 Strong main frame for high reliability  
 High built main frame for maximum ground clearance in transport and headland position  
 90 ° turning angle on headstock and wide angled PTO-shaft  
 Hydraulically operated swath board  
 Warning panels and lightning equipment  
 Duracoat powder paint

### Technical specifications

Type	Andex 1503
Working width	9,00 – 15,00 m
Swath width	1,40 – 2,50 m
Length	9,20 m
Transport width	2,98 m
Parking height with/without arms	3,99/ 3,45 m
Weight app.	5600 kg
Rotor diameter	3850 mm
Cam track diameter	400 mm
Required horsepower app.	65 kW(90 HP)
PTO-speed	540 rpm
Type of linkage pins	CAT. II
Number of rotors	4
Number of tine arms	13 front / 15 back
Number of tines per arm	5
Height adjustment	crank
Wheels/tyres	16x6.50-8 PR 6, 6 per rotor
Wheels tyres main frame	19.0/45 – 17 AW 10 PR
Axles	Tri-Axle Twin
Loading space (Quickset, m)	
Machines per crate	
Shipping dimensions (crate, m)	

## Andex 1503















