

Vicon Index 773

Standard specifications

Pro Line

Double rotor rakes

Radial pin clutch for protection (each rotor separately)

Removable tine arms

Foldable safety guards

Super-C Quality tines

Maintenance free gear box (no greasing point)

Top gear running in an oil bath

Adjustable cam track

Exchangeable tine arms

Mechanically height adjustment, operated from the front of the rotor

Bi-tangential tine arms

Strong main frame for high reliability

High built main frame for maximum ground clearance in transport and headland position

Forced steering of main wheels for excellent track following

90 ° turning angle on headstock and wide angled PTO-shaft

Swath board

Warning panels and lightning equipment

Duracoat powder paint

Technical specifications

Type	Andex 773
Working width	7,70 m
Swath width	variable
Length	8,30 m
Transport width	2,82 m
Parking height with/without arms	3,99/ 3,20 m
Weight app.	1990 kg
Rotor diameter	3650 / 3450 mm
Cam track diameter	400 mm
Required horsepower app.	40 kW(54 HP)
PTO-speed	540 rpm
Type of linkage pins	CAT. I + II
Number of rotors	2
Number of tine arms	12
Number of tines per arm	4
Height adjustment	crank
Wheels/tyres	16x6.50-8 PR 6
Wheels tyres main frame	10.0/80 - 12
Axles	TerraLink Quattro
Loading space (Quickset, m)	6
Machines per crate	1
Shipping dimensions (crate, m)	3,30x2,25x1,10







VICON 773