

VICON RF 119

Standard Specifications	
*Bale Chamber with 14 profiled rollers. *Pick up with baffle plate, 1,67 intake width *Powerlock tailgate locking with integrated gas accumulator *twine binding standard *Nylosring bearing protection	
Technical Specification	
Type	RF 119
Max. Bale weight	1.000 kg
Chamber size	1,22 x 1,25 m
Drawbar	High/low hitch
Total PU width	1,67 m
Wrapping system	Twine or Net
Tyres	10.0/75-15 AW
Drive	PTO with shear bolt
PTO Speed	540 RPM
Horsepower requirement	36 kW (50 HP)
Weight	1.800 kg
Dimensions	
Height	2215 mm
Width	2350 mm
Length	4430 mm
40' container	4 units in 1 container



VICON RF 121-R

Standard Specifications	
Technical Specification	
Type	RF 121-R
Max. Bale weight	1.200 kg
Chamber size	1,22 x 1,25 m
Drawbar	High/low hitch
Total PU width	1,85 m
PU width tine to tine	1,
Wrapping system	Twine /net /twine and net
Tyres	11.5/80x15.3
Drive	PTO with cam clutch
PTO Speed	540 RPM
Horsepower requirement	44 kW (60 HP)
Weight	2.380 kg
Dimensions	
Height	2280 mm
Width	2480 mm
Length	4430 mm
40' container	4 units in 1 container



Vicon RF 125

Standard Specifications

- *Bale Chamber with 14 profiled rollers.
- *Rollers with asymmetric BaleTrak roller profile for high density bales in all conditions.
- *Integral-Rotor intake system for maximum performance
- *2 different intake executions
 1. Feeding Rotor: **OptiFeed**
 2. Cutting Rotor with 14 knives: **OptiCut 14**
- *Nylosring bearing protection
- *Powerlock tailgate locking with integrated gas accumulator
- *Pick up with cam type clutch overload protection

Technical Specification

Type	RF 125 OptiFeed	RF 125 OptiCut 14
Max. Bale weight	1.200 kg	1.200 kg
Chamber size	1,22 x 1,25 m	1,22 x 1,25 m
Drawbar	High/low hitch	High/low hitch
Total PU width	2,10 m	2,10 m
PU width tine to tine	1,78 m	1,78 m
Wrapping system	Twine /net /twine and net	Twine /net /twine and net
Tyres	11.5/80x15.3	11.5/80x15.3
Drive	PTO with cam clutch	PTO with cam clutch
PTO Speed	540 RPM	540 RPM
Horsepower requirement	44 kW (60 HP)	44 kW (60 HP)
Weight	2380 kg	2480 kg
Dimensions		
Height	2280 mm	2280 mm
Width	2637 mm	2637 mm
Length	4430 mm	4430 mm
40' container	4 units in 1 container	4 units in 1 container

VICON MP 135

Standard Specifications			
<p>*Bale Chamber with 19 profiled rollers. *Integral-Rotor intake system for maximum performance *3 different intake executions 3. Feeding Rotor: OptiFeed (prepared for OC 14) 4. Cutting Rotor with 14 knives: OptiCut 14 5. Cutting Rotor with 23 knives: OptiCut 23 *Powerlock tailgate locking with integrated gas accumulator *5 tine row pick up with baffle plate and pneumatic tyred gauge wheels</p>			
Technical Specification			
Type	MP 135 OptiFeed	MP 135 OptiCut 14	MP 135 OptiCut 23
Max. Bale weight	1.200 kg	1.200 kg	1.200 kg
Chamber size	1,22 x 1,25 m	1,22 x 1,25 m	1,22 x 1,25 m
Drawbar	High/low hitch	High/low hitch	High/low hitch
Total PU width	2,10 m	2,10 m	2,30 m
PU width tine to tine	1,78 m	1,78 m	1,90 m
Wrapping system	Twine /net /twine and net	Twine /net /twine and net	Twine /net /twine and net
Tyres	11.5/80x15.3	11.5/80x15.3	11.5/80x15.3
Drive	PTO with cam clutch	PTO with cam clutch	PTO with cam clutch
PTO Speed	540/1000 RPM	540/1000 RPM	540/1000 RPM
Horsepower requirement	58 kW (80 HP)	58 kW (80 HP)	66 kW (90 HP)
Weight	2.500 kg	2.550 kg	2.975 kg
Dimensions			
Height	2560 mm	2560 mm	2560 mm
Width	2470 mm	2470 mm	2700 mm
Length	4170 mm	4170 mm	4170 mm
40' container	4 units in 1 container	4 units in 1 container	4 units in 1 container

Vicon RF 155

Standard Specifications

- *Bale Chamber with 17 profiled rollers.
- *Rollers with asymmetric BaleTrack roller profile for high density bales in all conditions.
- *Integral-Rotor intake system for maximum performance
- *3 different intake executions
- 6. Feeding Rotor:
- 7. Cutting Rotor with 14 knives: **OptiCut 14**
- 8. Cutting Rotor with 23 knives: **OptiCut 23**
- *Tandem axle possible
- *To the outside exchangeable bearings

Technical Specification

Type	RF 155	RF 155 OptiCut 14	RF 155 OptiCut 23
Max. Bale weight	1.800 kg	1.800 kg	1.800 kg
Chamber size	1,22 x 1,50 m	1,22 x 1,50 m	1,22 x 1,50 m
Drawbar	High/low hitch	High/low hitch	High/low hitch
Total PU width	2,10 m	2,10 m	2,30 m
PU width tine to tine	1,78 m	1,78 m	1,90 m
Wrapping system	Twine /net /twine and net	Twine /net /twine and net	Twine /net /twine and net
Tyres	15.0/55x17	15.0/55x17	15.0/55x17
Drive	PTO with cam clutch	PTO with cam clutch	PTO with cam clutch
PTO Speed	540/1000 RPM	540/1000 RPM	540/1000 RPM
Horsepower requirement	58 kW (80 HP)	58 kW (80 HP)	66 kW (90 HP)
Weight	2.975 kg	3.200 kg	3.450 kg
Dimensions			
Height	2560 mm	2560 mm	2560 mm
Width	2430 mm	2430 mm	2700 mm
Length	4370 mm	4370 mm	4370 mm
40' container	4 units in 1 container	4 units in 1 container	4 units in 1 container

