



WIL-RICH



Products

Dealer Locations

About Wil-Rich

Contact Us

357 Inline Ripper

[357](#) [Specifications](#) [Gallery](#) [Manuals](#)

With the 357, you determine furrow size and surface residue by combining different shanks and points and adjusting your operating speed. Ask your Wil-Rich [dealer](#) to help you pick the best setup for your soil type and farming practices.



Features

- Frame: 4" x 6 x 3/8" 2-bar
- Hitch: 3-Point or Pull-Type
- Rigid, flat fold, over center fold
- 35" under frame clearance
- Rigid or spring reset holders
- 3000 pound point pressure - spring reset
- Operating speeds: 4½ to 6 mph
- Shanks working depth: 16" maximum
- Parabolic or minimal disturbance shank
- Parabolic shanks: 1-1/4 x 3 High Strength Abrasion Resistant Steel
- Minimal Disturbance Shank: 1-1/4 x 4 shank
- Shank staggering brackets (optional)
- Gauge wheels: 20.5 x 10; 10 ply (optional)
- Coulters working depth: 7" maximum (optional)
- Coulters: 20" rippled
- 35 to 50 horsepower (PTO) per shank (suggested)
- Safety Equipment: Transport Warning Lights
- Parking stand (two required on 3pt models)



Products

[Field Cultivators](#)
[Rippers](#)
[Chisel Plows](#)
[Flail Shredders](#)
[Toolbars](#)
[Disk Cultivators](#)
[Combo Disk, Chisel, Ripper](#)
[Disk Harrows](#)
[Sprayers](#)
[Seedbed Finishers](#)
[Moldboard Plows](#)

Options

- Mounted or Pull Type
- 30" or 36" spacing
- 3, 4, 5, 6, 7, 8, or 12 shank units

Attachments



