



WIL-RICH



Products

Dealer Locations

About Wil-Rich

Contact Us

DCIII Disk Cultivator

A

[DCIII](#) [Specifications](#) [Gallery](#) [Video](#) [Manuals](#)

deep 5-bar frame with 31 inches between ranks allows the DCIII to operate in high residue conditions without plugging. With 125 inches between the front and rear row of shanks, combined with 9 inch shank spacing, gives you another way to save time and fuel with a one pass disk cultivator. The DCIII is an excellent choice for your seedbed preparation and chemical incorporation.



Products

[Field Cultivators](#)
[Rippers](#)
[Chisel Plows](#)
[Flail Shredders](#)
[Toolbars](#)
[Disk Cultivators](#)
[Combo Disk, Chisel, Ripper](#)
[Disk Harrows](#)
[Sprayers](#)
[Seedbed Finishers](#)
[Moldboard Plows](#)

Standard Features

- Level-Lift Hitch with Screw Adjustment
- 5-bar design with 3" x 4" tubing
- 125" front to rear frame depth
- Crank Adjustable Side Mount Gauge Wheels
- Heavy Duty Screw Type Jack
- Visual Gauge of Relative Shank Depth
- Single Point Depth Control Hydraulics
- 11ft. or 14 ft. main frames



Finishing Attachments

4-Bar Coil Tine Harrow:

- Formed channel tooth bars
- Easy tine replacement (two bolts)
- 7/16" diameter by 18" long tine
- Nine tine adjustments
- Five harrow leveling adjustments



Combination Coil Tine Harrow and Rolling Basket:

3-Bar Coil Tine Harrow:

- Formed channel tooth bars
- Easy Tine replacement (two bolts)
- 7/16" diameter by 18" long tine



- Multi-Tine Angle Adjustment
- Spring Dampened Parrallel Movement Tooth Bars



Rolling Basket:

- Single 14" diameter rolling basket
- 7/8" Diameter Tube Spiral Design
- Greaseable sealed bearings
- Quick removal of rear basket - pin and latch design

Shank Assemblies

The Edge Formed C-Shank

- 9/16" x 1 3/4" Shank
- 3/8" Extension Spring
- 3 1/4" Wide Pivot Point
- 16" Trip Clearance
- 24" Under Frame Clearance
- 47 Degree Shovels Required
- 120-150 lbs. Initial Point Pressure



C-Shank

- 3/4" x 1-3/4" Shank
- (2) 3/8" Extension Spring
- 16" Trip Clearance
- 3 1/4" Wide Pivot Point
- 24" Under Frame Clearance
- 47 Degree Shovels Required
- 240-300 lbs. Initial Point Pressure



Optional Attachments

- Mud Scraper Kit
- Hydraulic Extension Package
- Sweeps with Hardware
- Safety Light Extension Package
- Heavy Duty Rear Hitch