

## COMPARAISON ANCIEN vs NOUVEAU

ANCIEN <b>Quicke</b>	PUISSANCE	FORCE DE LEVAGE	FORCE DE LEVAGE	HAUTEUR DE LEVAGE	
	TRACTEUR	NIVEAU DU SOL	HAUTEUR MAXI	POINT PIVOT	
710	50-80 HP	2250 lbs / 1150 kg	1650 lbs / 750 kg	126" / 3.20 m	
	50-70 HP	2640 lbs / 1200 kg	2090 lbs / 950 kg	126" / 3.20 m	Q 20
720	50-80 HP	2650 lbs / 1200 kg	1750 lbs / 800 kg	138" / 3.50 m	
	50-80 HP	3080 lbs / 1400 kg	2530 lbs / 1150 kg	138" / 3.50 m	Q 30
740	60-90 HP	3100 lbs / 1400 kg	2200 lbs / 1000 kg	148" / 3.75 m	
750	70-100 HP	3750 lbs / 1700 kg	2750 lbs / 1250 kg	148" / 3.75 m	
755	70-100 HP	4180 lbs / 1900 kg	3190 lbs / 1450 kg	148" / 3.75 m	
1055	70-100 HP	4180 lbs / 1900 kg	3190 lbs / 1450 kg	148" / 3.75 m	
	60-100 HP	3850 lbs / 1750 kg	3190 lbs / 1450 kg	148" / 3.75 m	Q 40
760	70-100 HP	3400 lbs / 1550 kg	2450 lbs / 1100 kg	157" / 4.00 m	
	80-120 HP	4180 lbs / 1900 kg	3520 lbs / 1600 kg	157" / 4.00 m	Q 50
770	90-130 HP	5300 lbs / 2400 kg	3650 lbs / 1650 kg	157" / 4.00 m	
1065	90-130 HP	5300 lbs / 2400 kg	3650 lbs / 1650 kg	157" / 4.00 m	
	100-150 HP	4730 lbs / 2150 kg	4070 lbs / 1850 kg	167" / 4.25 m	Q 60
920	50-80 HP	3200 lbs / 1450 kg	2550 lbs / 1150 kg	130" / 3.30 m	
	50-80 HP	3300 lbs / 1500 kg	2640 lbs / 1200 kg	138" / 3.50 m	Q 35
930	50-80 HP	3550 lbs / 1600 kg	2550 lbs / 1150 kg	148" / 3.75 m	
940	60-90 HP	4200 lbs / 1900 kg	3300 lbs / 1500 kg	138" / 3.50 m	
	60-100 HP	4180 lbs / 1900 kg	3410 lbs / 1550 kg	148" / 3.75 m	Q 45
950	70-100 HP	4400 lbs / 2000 kg	3300 lbs / 1500 kg	158" / 4.00 m	
960	80-120 HP	4850 lbs / 2200 kg	3750 lbs / 1700 kg	148" / 3.75 m	
1060	80-120 HP	4850 lbs / 2200 kg	3750 lbs / 1700 kg	148" / 3.75 m	
	80-120 HP	4510 lbs / 2050 kg	3740 lbs / 1700 kg	157" / 4.00 m	Q 55
970	90-130 HP	5050 lbs / 2300 kg	3850 lbs / 1750 kg	157" / 4.00 m	
1070	90-130 HP	5050 lbs / 2300 kg	3850 lbs / 1750 kg	157" / 4.00 m	
	100-150 HP	5060 lbs / 2300 kg	4400 lbs / 2000 kg	167" / 4.25 m	Q 65
980	100-170 HP	5950 lbs / 2700 kg	4850 lbs / 2200 kg	167" / 4.25 m	
1080	100-170 HP	5950 lbs / 2700 kg	4850 lbs / 2200 kg	167" / 4.25 m	
	100-190 HP	5500 lbs / 2500 kg	4620 lbs / 2100 kg	177" / 4.50 m	Q 75
990	140-270 HP	6400 lbs / 2900 kg	5050 lbs / 2300 kg	181" / 4.60 m	
	from 150 HP	6600 lbs / 3000 kg	4950 lbs / 2250 kg	187" / 4.75 m	Q 85

Force de levage à 31,5" / 800 mm en avant du point pivot

\* Varie selon l'accessoire.

Les spécifications ci-hauts sont basées sur les plus récentes normes standards ASAE 301.3.